Serial No. 10/691,615 Amdt. dated <u>September 27, 2006</u> Reply to Office Action of <u>June 30, 2006</u>

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

(Currently Amended) An automatic gain control method comprising:
 extracting a maximum absolute value of a reception signal received by a receiver
 of a radio frequency communication system;

determining a gain control value of the reception signal on the basis of the maximum absolute value and a predetermined threshold; and

controlling gain of the reception signal according to the determined gain control valuevalue.

wherein the abstracting the maximum absolute value comprises storing absolute values of the reception signal and extracting the maximum absolute value from among the stored absolute values.

- 2. (Canceled)
- 3. (Currently Amended) The method of claim 1, wherein the step of controlling the gain comprises:

Serial No. 10/691,615 Amdt. dated <u>September 27, 2006</u> Reply to Office Action of <u>June 30, 2006</u>

amplifying the reception signal by multiplying the reception signal by the determined gain control value; and

outputting the amplified reception signal.

- 4. (Original) The method of claim 1, wherein the gain control value is for amplifying the reception signal to make the extracted maximum absolute value consist with the predetermined threshold, and the predetermined threshold is a maximum absolute value of a predetermined reception signal.
- 5. (Currently Amended) An automatic gain control apparatus of a radio frequency communication system comprises the means for:

a means for extracting a maximum absolute value of a reception signal received by a receiver of a radio frequency communication system;

a means for determining a gain control value of the reception signal on the basis of the maximum absolute value and a predetermined threshold; and

a means for controlling gain of the reception signal according to the determined gain control value; and

a means for storing absolute values of the reception signal,
wherein the means for extracting the maximum absolute value extracts the

Serial No. 10/691,615
Amdt. dated September 27, 2006
Reply to Office Action of June 30, 2006

maximum absolute value from among the stored absolute values.

6. - 7. (Canceled)

- 8: (Original) The apparatus of claim 5, wherein the means for controlling the gain amplifies the reception signal by multiplying the reception signal by the determined gain control value, and outputs the amplified reception signal.
- 9. (Original) The apparatus of claim 5, wherein the means for determining a gain control value of the reception signal determines a gain control value for amplifying the reception signal to make the abstracted maximum absolute value consist with the predetermined threshold, wherein the threshold is a maximum absolute value of a predetermined reception signal.
- 10. (Currently Amended) An automatic gain control apparatus of a radio frequency communication system comprises comprising:

an amplitude controller for calculating absolute values of a reception signal received by a receiver of a radio frequency communication system;

a buffer for storing the absolute values of the reception signal, which have been calculated by the amplitude controller;

Docket No. P-0605

Serial No. 10/691,615

Amdt. dated <u>September 27, 2006</u>

Reply to Office Action of June 30, 2006

a controller for extracting a maximum absolute value among the absolute values

stored at the buffer, and determining a gain control value of the reception signal by comparing

the extracted maximum absolute value with a predetermined threshold; and

a multiplier for amplifying the reception signal by multiplying the reception signal

by the determined gain control value, and outputting the amplified reception signal.

11. (Original) The apparatus of claim 10, wherein the buffer is a first-in first-out

storage.

12. (Currently Amended) The apparatus of claim 10, wherein the gain control value is

for amplifying amplifies the reception signal to make making the extracted maximum absolute

value consist consistent with the predetermined threshold, and the predetermined threshold is

being a maximum value of a predetermined reception signal.

5